

HIGH PRESSURE WIRE HOSES WITH PA11 CORE TUBE

HIGH PRESSURE WIRE HOSES WITH PA11 CORE TUBE

1/4" 6,250 psi High pressure wire hose

2240N-04V91



CONSTRUCTION	<p>Core tubeMethanol washed PA11</p> <p>Pressure reinforcementHigh strength wire</p> <p>CoverPA12</p> <p>ColourBlack</p>
TEMPERATURE RANGE	<p>-40°C up to +100°C, max. 70°C for water or methanol based fluids.</p> <p>-40°F up to +212°F, max. 158°F for water or methanol based fluids.</p>
MAX. LENGTH	<p>3,200 m / 10,499 ft</p> <p>(for longer length requirements please contact Parker Hannifin)</p>
SPECIFICATION	<p>Meets or exceeds performance requirements of ISO 13628-5 / API 17E</p>


2240N-04V91

⊙		⊙		⊙		⊙		↷		⊙		Collapse pressure		DF
mm	inch	mm	inch	MPa	psi	MPa	psi	mm	inch	kg/m	lbs/ft	MPa	psi	
6.5	1/4	11.6	0.460	43	6,250	172.5	25,000	70	2.8	0.17	0.11	10	1,450	4.0

JIC female swivel

Material: AISI 316 / 316Ti

#	⊙	A		B		H	⊙	
		mm	inch	mm	inch		mm	MPa
106RX-4-04C	7/16 - 20 UNF	52.0	2.05	23.0	0.91	17	43.0	6,250
106RX-6-04C	9/16 - 18 UNF	53.5	2.11	24.5	0.96	19	43.0	6,250



BSP female swivel (60° cone)

Material: AISI 316 / 316Ti

#	⊙	A		B		H	⊙	
		mm	inch	mm	inch		mm	MPa
192RX-4-04C	G 1/4	50.5	1.99	22.0	0.87	17	43.0	6,250

