

1/4" 10,000 psi High pressure ChemJec hose 2340M-04V38



C

CONSTRUCTION

Core tube Fluoropolymer based core tube
Pressure reinforcement High strength wire

Cover PA12
Colour Golden

TEMPERATURE RANGE

-40°C up to +100°C
 -40°F up to +212°F
 For higher temperature requirements please contact Polyflex Division

MAX. LENGTH

5,000 m / 16,404 ft
 (for longer length requirements please contact Parker Hannifin)

SPECIFICATION


Meets or exceeds performance requirements of ISO 13628-5 / API 17E

2340M-04V38


												Collapse pressure		DF
mm	inch	mm	inch	MPa	psi	MPa	psi	mm	inch	kg/m	lbs/ft	MPa	psi	
6.4	1/4	12.5	0.490	69	10,000	276.0	40,000	70	2.8	0.23	0.15	20.5	2,973	4.0

JIC female swivel**Material: AISI 316 / 316Ti**


#		A		B			
		mm	inch	mm	inch	mm	psi
1068X-4-04C	7/16 - 20 UNF	57.0	2.244	26.0	1.024	19	10,000
1068X-6-04C	9/16 - 18 UNF	55.0	2.165	24.0	0.945	19	15,000

**BSP female swivel (60° cone)****Material: AISI 316 / 316Ti**

#		A		B			
		mm	inch	mm	inch	mm	psi
1928X-4-04C	G 1/4	56.0	2.205	25.0	0.984	19	11,600

**Type M female swivel****Material: AISI 316 / 316Ti**

#		A		B			
		mm	inch	mm	inch	mm	psi
1AY8X-6-04C	9/16 - 18 UNF	66.0	2.598	33.0	1.300	19	15,000

**Medium pressure tube nipple****Material: AISI 316 / 316Ti**

#		A		B		
		mm	inch	mm	inch	psi
1Y28X-6-04C	3/8 - 24 UNF - LH	120.0	4.724	87.0	3.425	20,000

