

# 1-1/2" - 5,000\* psi Oil & Gas Hose

2340N-24V10



Oilfield Service Hose  
is ParKrimpable

## Construction

- Core Tube: Polyamide 11
- Pressure Reinforcement: Two spiral layers of high tensile steel wire
- Cover: Polyurethane

## Temperature

- Temperature Range:  
-40°F to 212°F (-40°C to 100°C)\*\*

## Certifications

- ISO 13628-5

## Design Factor

- 4


## Notes

- \*\*Operating temperature will vary depending on the fluid. Consult Parker for more information.

[Visit the webpage](#)

Part Number	Nominal I.D.				Max. O.D.		Max. Working Pressure		Min. Bend Radius		Weight		Fitting Series
	DN	Size	inch	mm	inch	mm	psi	bar	inch	mm	lbs./ft.	kg/mtr	
2340N-24V10	40	-24	1-1/2	38.1	2.19	55.5	5,000	345	17.7	450	2.4	3.5	8X

## 1068X - JIC 37° Female Flare



Part Number	Nominal I.D.				Thread Size	Overall Length A		Cutoff Allow. B		H Hex		J Hex	
	DN	Size	inch	mm		inch	mm	inch	mm	inch	mm	inch	mm
1068X-24-24C	40	-24	1-1/2	38.1	1-7/8" - 12 UN	6.82	173	3.51	89	2.56	65	2.16	55

C - All components Stainless Steel



## WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).