


HIGH PRESSURE WIRE HOSES WITH PA11 CORE TUBE

3/8" 6,250 psi High pressure wire hose

2370N-06V91

**CONSTRUCTION**

Core tubeMethanol washed PA11
 Pressure reinforcementHigh strength wire, synthetic fibre

CoverPA12
 ColourBlack

TEMPERATURE RANGE

-40°C up to +100°C, max. 70°C for water or methanol based fluids.
 -40°F up to +212°F, max. 158°F for water or methanol based fluids.

MAX. LENGTH

2,200 m / 7,218 ft
 (for longer length requirements please contact Parker Hannifin)

SPECIFICATION


Meets or exceeds performance requirements of ISO 13628-5 / API 17E

2370N-06V91

⊙		⊙		⊙		✂		↩		Ⓜ		Collapse pressure		DF
mm	inch	mm	inch	MPa	psi	MPa	psi	mm	inch	kg/m	lbs/ft	MPa	psi	
9.9	3/8	16.5	0.650	43	6,250	172.5	25,000	120	4.7	0.33	0.22	9.4	1,363	4.0

JIC female swivel**Material: AISI 316 / 316Ti**

#	⚡	A		B		Ⓜ	⊙	
		mm	inch	mm	inch		mm	MPa
106NX-6-06C	9/16 - 18 UNF	58.0	2.28	28.0	1.10	19	43.0	6,250

**BSP female swivel (60° cone)****Material: AISI 316 / 316Ti**

#	⚡	A		B		Ⓜ	⊙	
		mm	inch	mm	inch		mm	MPa
192NX-6-06C	G 3/8	55.0	2.17	25.0	0.98	22	43.0	6,250

