







2388N – High pressure hose



- CONSTRUCTION**
- Core tube** : Polyamide
 - Pressure reinforcement** : Two spiral layers and two open spiral layers of high tensile steel wire
 - Cover** : Polyurethane
 - Standard colour** : V00: Black; V12: Blue


TEMPERATURE RANGE -40°C up to +100°C

Design Factor 4:1

#												
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m	
2388N-04V00	6	-04	6.3	1/4	13.4	80	11600	320	46400	80	0.30	
2388N-06V12	10	-06	10,1	3/8	19,8	72	10440	288	41760	100	0,65	

NOTES -

2388N – High pressure hose



- CONSTRUCTION**
- Core tube** : Polyamide
 - Pressure reinforcement** : Two spiral layers and two open spiral layers of high tensile steel wire
 - Cover** : Polyurethane
 - Standard colour** : Blue

TEMPERATURE RANGE -10°C up to +70°C

#													Fittings Series
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m		
2388N-04V12W	6	-04	6.3	1/4	13.4	128	18.560	320	46400	80	0.30	KY	
2388N-06V12W	12	-06	10.1	3/8	19.8	125	18.125	312.5	45310	100	0.65	BS	
2388N-08V12W	12	-08	13.0	1/2	23.0	110	15950	275	39875	120	0.80	BS	



NOTES