

# 518D - Non-Conductive Hose



## Construction

- Tube: Nylon: -2 to -12 Copolyester: -16
- Reinforcement: Fiber
- Cover: Polyurethane

## Fittings

- 561R Series 56 Series
- For most Parker products, Crimp Die Selection charts are found online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Operating Parameters

- Temperature Range(except 518D-16):  
-40°F (-40°C) to 212°F (100°C)
- 518D-16 Temperature Range:
  - ◆ Petroleum based hydraulic fluids and lubricating oils within a temperature range -70°F (-57°C) to 212°F (100°C)
  - ◆ Synthetic, synthetic blend, water, and water/oil emulsion hydraulic fluids limited to 135°F (57°C)
- Vacuum Rating: 28 inch Hg
- Change in length at Max. Working Pressure: +/-2%
- Min. Burst Pressure: (SAE requires 4:1 Design Factor)
  - 4:1 design factor required per SAE J517 100R7
  - 3:1 min design factor acceptable per ANSI A92.2

## Features

- Nylon core for maximum resistance to permeable fluids
- -4 construction features:
  - ◆ Super high density braid resulting in compact braid O.D.
  - ◆ Heavier polyurethane jacket improving abrasion resistance and multi/twin-line separation for bonded assemblies
- Low coefficient of friction cover
- Twin or multi-line constructions available
- Approved for use with 51R-Series Field Attachable and Rapid Assembly connections

## Compliance

- Meets SAE J517 electrical standards (non-conductivity)
- Meets/Exceeds SAE J517 100R7
- DNV-GL Type Approved
- ANSI A92.2
- ISO 3949-R7-2

## Notes

- Non-perforated cover
- Lay lines on this hose will have both ANSI and SAE maximum working pressure listed. ANSI A92.2 "Vehicle Mounted Elevating and Rotating Aerial Devices"
- Field attachable fittings are not intended for use on hose that has been previously in service

## Color

- ● Orange (non-conductive)

## Series 518D

[Visit the webpage](#)

Part Number	Nominal I.D.		Maximum O.D.		ANSI A92.2 Maximum Working Pressure		SAE 100R7 Maximum Working Pressure		Minimum Bend Radius		Weight		Perm. Fitting Series	Field Attach. Fitting Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	kg/mtr		
518D-2	1/8	3.2	0.34	8.6	3,150	21.7	3,000	21	1/2	13	0.03	0.05	56	-
518D-3	3/16	5	0.43	10.9	3,250	22.4	3,250	22.4	3/4	19	0.05	0.07	56	51R
518D-4	1/4	6.3	0.47	11.9	3,150	21.7	3,000	21	1-1/2	38	0.06	0.09	56	51R
518D-5	5/16	8	0.57	14.5	3,150	21.7	2,500	17.5	1-3/4	44	0.08	0.11	56	-
518D-6	3/8	10	0.64	16.3	3,000	21	2,250	15.8	2	51	0.1	0.14	56	51R
518D-8	1/2	12.5	0.81	20.6	3,000	21	2,250	15.8	3	76	0.15	0.22	56	51R
518D-10	5/8	16	0.98	24.9	3,000	21	2,250	19.2	6	152	0.21	0.31	56	-
518D-12	3/4	19	1.09	27.7	1,660	11.4	1,250	8.8	5	127	0.21	0.31	56	-
518D-16	1	25	1.32	33.5	1,330	9.2	1,000	7	8	203	0.27	0.4	56	-

