

PURETransfer

7620


[view on web page](#)

Series 7620 is a high quality delivery and suction hose. This series offers an antistatic tube allowing for transfer of dry abrasives. Tube material consists of premium nitrile (NBR).

# Part Number	 Hose ID		 Hose OD		 Vacuum		 Max. Working Pressure		 Min. Burst Pressure		 Weight		 Bend Radius	
	in	mm	in	mm	in of Hg	kPa	psi	bar	psi	bar	lbs/ft	kg/m	in	mm
7620-1000	1	25	1.5	37	26.5	90	90	6	270	18	0.54	0.80	4.92	125
7620-1500	1.5	38	2	51	26.5	90	90	6	270	18	0.87	1.29	8.27	210
7620-2000	2	51	2.6	66	26.5	90	90	6	270	18	1.29	1.93	12	300
7620-3000	3	76	3.62	92	26.5	90	90	6	270	18	2.18	3.25	18	450
7620-4000	4	102	4.65	118	26.5	90	90	6	270	18	2.99	4.47	24	600

WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

All PURETransfer hoses comply with the following standards:



Tube: White Antistatic Nitrile, phthalates free

Temperature: -13°F / +176°F (-25°C / +80°C)

Reinforcement: Synthetic plies, galvanized wire helices, on request a/s wires to discharge static electricity.

Cover: Black EPDM, Conductive, Smooth wrapped finish, **PURE** ozone, aging resistant

Sterilization: Refer to Parker's guidelines for cleaning and sanitizing.

ISO 1307: For dimensional tolerances.

Applications: Dry abrasives