

Parker Green Label™ Tank Truck Hose



Series 7705

Parker Green Label Tank Truck Hose is extremely flexible and light weight. It is designed for easy handling during the transfer of biodiesel fuels to B100, and ethanol, in transport and fixed in-plant applications. Produced in 100-ft. lengths up to 4-inch I.D. as standard, Green Label Tank Truck Hose is also available in larger sizes, longer lengths and color variations on a special-order basis.

- **Flexible rubber hose for the transfer of alternative fuels, easily accommodates difficult routing in plant applications.**
- **Light weight, for easy handling by in-plant staff and product transporters.**
- **200 psi working pressure, at a 4:1 Design Factor, up to and including 3" I.D. hose.**
- **Full suction capabilities.**
- **Modified tube compound provides compatibility in the most difficult alternative fuel applications up to B100 blends meeting BQ-9000 standards.**
- **Opportunity to have crimped fitting qualifications developed to create a system backed by Parker, the world leader in hose manufacturing.**

Packaging

Standard packaging is 100-foot coils. Lengths available up to 200-feet upon request.

Couplings

Refer to CrimpSource at www.safehose.com for crimp specifications and coupling recommendations.

Green Label™ Tank Truck Hose • Series 7705

Tube:	Black nitrile
Reinforcement:	Multiple textile plies with helix wire(s)
Cover:	Black nitrile/PVC
Temp Range:	-20°F to +180°F (-29°C to +82°C)
Brand Method:	Black text on green stripe
Brand Example:	PARKER SERIES 7705 GREEN LABEL TANK TRUCK HOSE 200 PSI MAX WP MADE IN USA
Vacuum Rating:	Full



Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Length (ft)
7705-1000	1	25.4	2	1.437	36.5	55	2.0	200	100
7705-1250	1-1/4	31.8	2	1.693	43.0	70	2.5	200	100
7705-1500	1-1/2	38.1	2	1.969	50.0	83	3.0	200	100
7705-2000	2	50.8	2	2.44	62.0	100	4.0	200	100
7705-2500	2-1/2	63.5	2	2.953	75.0	137	5.0	200	100
7705-3000	3	76.2	2	3.488	88.6	175	5.0	200	100
7705-4000	4	102.0	2	4.527	115.0	233	6.0	150	100