

792PM / SPIRAFLEX

Hydraulic
SAE 100 R15



# Part Number	Hose I.D.		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	bar	inch	mm	lbs/ft	kg/m
792PM-12PM	3/4	19.0	28.4	32.0	6000	420	10.5	265	1.08	1.60
792PM-16PM	1	25.4	35.2	38.5	6000	420	13.0	330	1.41	2.10
792PM-20PM	1-1/4	31.8	46.8	49.6	6000	420	17.5	445	2.62	3.90
792PM-24PM	1-1/2	38.1	54.3	57.1	6000	420	21.0	530	3.43	5.11

* Impulse test conducted with Parker Fittings.

Application:

Recommended for very high pressure hydraulic power lines. Constant pressure on all hose sizes.

Construction:

Inner tube : CR - Synthetic rubber
Reinforcement : Four or six high tensile steel wire spirals
Outer Cover : SBR - Synthetic rubber

Temp. Range

- 40°C to +125°C
(-40°F to +257°F)

Impulse Cycles:

Specified - 5,00,000 cycles
Tested up to - 10,00,000 cycles

Markets



Construction



Grounds & Building
Maintenance



Utility
Equipment



Machine Tool



Oil Field Service



Paving & Road
Maintenance



Ground Support
Equipment



Industrial

Type Approvals: MED