

PVC TUBING



ANFO EXPLOSIVES LOADING HOSE

Specifically designed tubing used for the delivery of pneumatically loaded explosives up blast holes. Manufactured from materials with specific lowstatic properties, to enable its use with explosives. The tube is semi rigid allowing it to be coiled for ease of transport and storage but able to self support itself, a feature required in applications of long upholes where explosive needs to be loaded at the top of the hole. Upholes of up to 150 feet have been loaded using this tube. Manufactured to meet the requirements of AS 2187.2—Explosives—Storage, Transport, and Use. Part 2 use of explosives.



ANFO 20MM—SEMI RIGID MATERIAL: VIRGIN PVC

ID (mm)	OD (mm)	Wall Thickness (mm)	Resistance (1m)	Total Resistance (coil)	Weight (kg/mt)	Part No
19.0	27.0	4.04	15-25kΩ	<1.6MΩ	0.35	ANFO-020-***

Temp Range:	Min -21°C to Max +60°C
Colour:	Orange with Black stripe and Tube

ANFO 25MM & 32MM—RIGID MATERIAL: SEMI CONDUCTIVE HIGH DENSITY POLYETHYLENE (HPDE)

ID (mm)	OD (mm)	Wall Thickness (mm)	Resistance (1m)	Total Resistance (coil)	Weight (kg/mt)	Part No
25.4	30.0	2.49	15-25kΩ	<1.6MΩ	0.22	ANFO-025-***
32.0	37.0	2.50	15-25kΩ	<1.6MΩ	0.28	ANFO-032-***

Temp Range:	Min -21°C to Max +80°C
Colour:	Orange with Black stripe and Tube

*** To complete part number, add coil length.

All W.P. ratings are at 20°C.