



APERFRUT 20 - 40 - 80

For delivery of air, water and all fungicide products. Particularly suitable for spraying in agriculture. Resistant to compressor oil-mist.

Hose Construction

Tube: Black, smooth, PVC compound
Reinforcement: Synthetic textile yarns
Cover: Orange (20), red (40) and blue (80), smooth, abrasion, and weather-resistant PVC compound

Temperature Range

-15 °C (+5 °F) to +60 °C (+140 °F)



- Colored cover to distinguish WP level
- Multiple fluids for various industrial applications
- Design Factor 3:1 for 20 and 40 bar
- Design Factor 2.5:1 for 80 bar

Tolerances

Refer to Technical Handbook on page TH34

Part Number			 Max. Working Pressure			 Weight	 min. Bend Radius
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	mm
APERFRUT 20							
IH35040014/100	13	19	2.0	300.0	20	0.22	70
IH35040016/100	19	26.5	2.0	300.0	20	0.38	100
APERFRUT 40							
IH35040261/100	10	16	4.0	600.0	40	0.19	50
APERFRUT 80							
IH35040268/100	8	15	8.0	1200.0	80	0.17	40
IH35040270/100	10	18	8.0	1200.0	80	0.26	50
IH35040214/100	13	21	8.0	1200.0	80	0.38	70

Hose layline example

APERFRUT 20 bar PARKER
APERFRUT 40 bar PARKER
APERFRUT 80 bar PARKER