

C064SH

DIN20023 4SH/EN856



Application: Petroleum base hydraulic and lubricating oils

Inner Tube: Synthetic rubber

Reinforcement: Four spiral steel wire

Cover: Synthetic rubber

Temperature Range: -40°C to +100°C

# Part Number	Hose I.D.					Wire O.D.		Hose O.D.		Working Pressure		Burst Pressure		Min.Bend Radius	Weight
	DN	inch	Dash	mm		mm		mm		MPa	psi	MPa	psi	mm	kg/m
				min	max	min	max	min	max						
C064SH-19	19	3/4	-12	18.6	19.8	27.6	29.2	31.4	33.0	42.0	6050	168.0	24400	280	1.64
C064SH-25	25	1	-16	25.0	26.4	34.4	36.0	37.5	39.9	38.0	5500	152.0	22000	340	2.10
C064SH-32	32	1-1/4	-20	31.4	33.0	40.9	42.9	43.9	47.1	32.5	4700	130.0	18800	460	2.74
C064SH-38	38	1-1/2	-24	37.7	39.3	47.8	49.8	51.9	55.1	29.0	4200	116.0	16800	560	3.75
C064SH-51	51	2	-32	50.4	52.0	62.2	64.2	66.5	69.7	25.0	3600	100.0	14500	700	5.01