

C064SP

DIN20023 4SP/EN856



Application: Petroleum base hydraulic and lubricating oils
Inner Tube: Synthetic rubber
Reinforcement: Four spiral steel wire
Cover: Synthetic rubber
Temperature Range: -40°C to +100°C

# Part Number	 Hose I.D.					 Wire O.D.		 Hose O.D.		 Working Pressure		 Burst Pressure		 Min. Bend Radius	 Weight
	DN	inch	Dash	mm		mm		mm		MPa	psi	MPa	psi	mm	kg/m
				min	max	min	max	min	max						
C064SP-10	10	3/8	-6	9.3	10.1	16.9	18.1	20.6	22.2	44.5	6450	178.0	25800	180	0.72
C064SP-13	13	1/2	-8	12.3	13.5	19.4	21.0	23.8	25.4	41.5	6000	166.0	24100	230	0.88
C064SP-16	16	5/8	-10	15.5	16.7	23.0	24.6	27.4	29.0	35.0	5050	140.0	20300	250	1.06
C064SP-19	19	3/4	-12	18.6	19.8	27.4	29.0	31.4	33.0	35.0	5050	140.0	20300	300	1.63
C064SP-25	25	1	-16	25.0	26.4	34.5	36.1	38.5	40.9	28.0	4050	112.0	16200	340	2.05
C064SP-32	32	1-1/4	-20	31.4	33.0	45.0	47.0	49.2	52.4	21.0	3000	84.0	12200	460	3.30
C064SP-38	38	1-1/2	-24	37.7	39.3	51.4	53.4	55.6	58.8	18.5	2650	74.0	10700	560	4.25