

PVC SUCTION HOSE CHEMICAL



CFX CROPFLEX

This extremely flexible medium duty hose is suitable for suction and low pressure delivery. Parker's unique PVC compound formulation provides superior resistance to mild chemicals and petroleum based products. It is designed to maintain flexibility at -10°C for ease of handling. Suitable for use on agricultural and chemical spraying equipment, suction and discharge on environmental waste collection tankers and in water transfer applications.



FEATURES:

- ♦ Excellent cold weather flexibility
- ♦ Good crush resistance
- ♦ Black UV stabilized
- ♦ Chemical and petrol resistant
- ♦ Australian made

ID (mm)	OD (mm)	Working Pressure (psi)	Vacuum Rating (mmHg)	Min Bend Radius (mm)	Weight (kg/mtr)	Part No
25.5	31.5	130psi	515	70	0.41	CFX-025-***
32.2	38.6	120psi	515	110	0.46	CFX-032-***
38.5	45.5	105psi	600	150	0.61	CFX-038-***
51.2	59.8	95psi	600	210	0.87	CFX-050-***
64.4	74.4	80psi	600	290	1.23	CFX-063-***
76.2	86.6	75psi	600	350	1.51	CFX-075-***

ID & OD dimensions are subject to the following tolerances: +/- 0.5 mm

Temp Range:	Min -10°C to Max +60°C
Tube/Cover Compound:	Flexible / High Impact Rigid PVC
Colour:	Black
Ink Branding:	PARKER CFX CROPFLEX (SIZE)MM MADE IN AUSTRALIA (DATE)

*** To complete part number, add coil length. Recommended safety factor 3:1. All W.P. ratings are at 20°C.