

PVC TUBING PRODUCTS



CVT CLEAR VINYL TUBING

Parker Clear Vinyl Tubing conforms to the requirements of AS/NZS 2070 for food contact. It is suitable for food and beverage lines operating at low pressures, general purpose low pressure delivery lines, syphon lines, cable protection and drainage lines. The clear nature of this product allows any materials being transferred to be easily seen and identified.



FEATURES:

- ♦ Clear PVC for ease of inspection
- ♦ Excellent flexibility
- ♦ Kink resistant
- ♦ Meets AS/NZS 2070
- ♦ Australian made

ID (mm)	OD (mm)	Working Pressure (psi)	Min Bend Radius (mm)	Weight (kg/mtr)	Coil Lengths (Mtrs)	Part No
3.0	5.0	n/a	50	0.02	8, 30	CVT-003-***
5.0	8.0	n/a	55	0.04	8, 30	CVT-005-***
6.0	9.0	n/a	65	0.05	8, 30	CVT-006-***
8.0	11.0	n/a	75	0.06	8, 30	CVT-008-***
10.0	13.0	n/a	85	0.07	4, 30	CVT-010-***
12.5	15.5	n/a	100	0.08	4, 30	CVT-012-***
16.0	19.0	n/a	130	0.10	30	CVT-016-***
20.0	24.0	n/a	150	0.17	30	CVT-020-***
25.0	30.0	n/a	180	0.27	30	CVT-025-***
32.0	38.0	n/a	220	0.40	30	CVT-032-***
40.0	47.0	n/a	250	0.58	15, 30	CVT-038-***
50.0	58.0	n/a	320	0.83	15, 30	CVT-050-***

ID & OD dimensions are subject to the following tolerances:
6-20mm +/- 0.4mm, 25-32mm +/- 0.6mm, 38-50mm +/- 1.0mm

Temp Range:	Min -10°C to Max +60°C
Tube/Cover Compound:	Virgin PVC
Colour:	Clear with blue tint
Ink Branding:	PARKER (SIZE)MM CVT FOOD CONTACT AS2070/ PETROL RESISTANT AUSTRALIA (DATE)

*** To complete part number, add coil length.