



DRINKPRESS WB/L 10

Designed for delivery of all foodstuffs containing vegetable fats and fluids as well as beverages such as wine, fruit juices and liqueurs. Also suitable for wash-down in food processing with hot water.

Hose Construction

Tube: White, smooth, NBR food quality rubber compound

Reinforcement: High tensile synthetic yarns

Cover: Blue, smooth, abrasion, vegetable fats, ozone and weather resistant NBR/PVC rubber compound

Temperature Range

-30 °C (-22 °F) to +110 °C (+230 °)



- Multipurpose food grade hose
- According to FDA 21 – EC 1935/2004
- Versatility of use, food transfer, wash-down applications
- Design Factor 3:1

Tolerances

According to UNI EN ISO 1307/97
Refer to Technical Handbook on page TH34

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource-euro.

Part Number			 Max. Working Pressure			 Weight	 min. Bend Radius
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	mm
IH30240022/40	10	19	1	150	10	0.31	80
IH30240020/40	13	23	1	150	10	0.42	105
IH30240025/40	16	26	1	150	10	0.49	130
IH30240030/40	19	30	1	150	10	0.71	150
IH30240035/40	25	36	1	150	10	1.05	200

Hose layline example