


1018X- NPT male


MATERIAL Carbon steel zinc plated, stainless steel on request



#						A	B			
	DN	size	mm	inch		mm	mm		MPa	psi
1018X-2-025	4	-025	4.0	5/32	1/8 NPT	51	24	8	103.5	15000
1018X-4-025	4	-025	4.0	5/32	1/4 NPT	59	32	13	103.5	15000

1928X - BSP female swivel (60° cone)


MATERIAL Carbon steel zinc plated, stainless steel on request



#						A	B			
	DN	size	mm	inch		mm	mm		MPa	psi
1928X-4-025	4	-025	4.0	5/32	G 1/4	48	20	19	140	20300

1A18X
- Type "M" female swivel


MATERIAL Carbon steel zinc plated, stainless steel on request



#						A	B			
	DN	size	mm	inch		mm	mm		MPa	psi
1A18X-6-025	4	-025	4.0	5/32	9/16 - 18 UNF	56	28	19	140	20300


1C98X - Metric female swivel heavy
series with o-ring

MATERIAL Carbon steel zinc plated, stainless steel on request



#						A	B			
	DN	size	mm	inch		mm	mm		MPa	psi
1C98X-8-025	4	-025	4.0	5/32	M16x1.5	54	27	19	150	21750

1AYJX – Type “M” female swivel




MATERIAL Nipple: very high strength stainless steel

Shell and nut: high strength carbon steel, zinc plated C-stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1AYJX-16-12C	20	-12	19.0	3/4	1 5/16-12UNF	90	31	41	160	23200
1AYJX-16-12W	20	-12	19.0	3/4	1 5/16-12UNF	90	31	41	160	23200


101KY - NPT male



MATERIAL Carbon steel zinc plated, C-stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
101KY-2-04	6	-04	6.4	1/4	1/8 NPT	56	29	10	103.5	15000
101KY-4-04	6	-04	6.4	1/4	1/4 NPT	62	35	13	103.5	15000
101KY-4-04C	6	-04	6.4	1/4	1/4 NPT	62	35	13	103.5	15000
101KY-6-04C	6	-04	6.3	1/4	3/8 NPT	62	35	17	103.5	15000
101KY-4-05	8	-05	7.9	5/16	1/4 NPT	69	35	13	103.5	15000
101KY-6-05	8	-05	7.9	5/16	3/8 NPT	69	35	17	103.5	15000


192KY - BSP female swivel (60° cone)



MATERIAL Carbon steel zinc plated, C-stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
192KY-6-05	8	-05	7.9	5/16	G 3/8	64	25	27	140	20300
192KY-8-06	10	-06	9.8	3/8	G 1/2	67	22	30	140	20300
192KY-8-06C	10	-06	9.8	3/8	G 1/2	67	22	30	140	20300


1AYKY - Type "M" female swivel



MATERIAL Carbon steel zinc plated, C-stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1AYKY-6-04	6	-04	6.4	1/4	9/16 - 18 UNF	61	30	22	140	20300
1AYKY-6-04C	6	-04	6.4	1/4	9/16 - 18 UNF	61	30	22	140	20300
1AYKY-8-05	8	-05	7.9	5/16	3/4 - 16 UNF	70	31	27	140	20300
1AYKY-8-06	10	-06	9.8	3/8	3/4 - 16 UNF	71	26	27	140	20300
1AYKY-8-06C	10	-06	9.8	3/8	3/4 - 16 UNF	71	26	27	140	20300


1C9KY - Metric female swivel heavy series with o-ring



MATERIAL Carbon steel zinc plated, C-stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1C9KY-10-04	6	-04	6.4	1/4	M18x1.5	68	36	22	150	21750
1C9KY-16-04	6	-04	6.4	1/4	M24x1.5	70	44	30	150	21750
1C9KY-16-04C	6	-04	6.4	1/4	M24x1.5	70	44	30	150	21750
1C9KY-12-05	8	-05	7.9	5/16	M20x1.5	70	31	24	150	21750
1C9KY-14-05	8	-05	7.9	5/16	M22x1.5	68	29	27	150	21750
1C9KY-16-05	8	-05	7.9	5/16	M24x1.5	77	38	30	150	21750
1C9KY-14-06	10	-06	9.5	3/8	M22x1.5	76	30	30	150	21750
1C9KY-14-06C	10	-06	9.5	3/8	M22x1.5	76	30	30	150	21750


1D9KY – BSP male 60° cone



MATERIAL Carbon steel zinc plated, stainless steel on request

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1D9KY-4-04	6	-04	6.3	1/4	G 1/4	62	36	19	140	20300

1U0KY – BSP female swivel (ballnose)




MATERIAL Carbon steel zinc plated, C: Stainless steel


#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1U0KY-4-04	6	-04	6.3	1/4	G 1/4	51	25	17	140	20300
1U0KY-4-04C	6	-04	6.3	1/4	G 1/4	51	25	17	140	20300

Design Factor >2:1


1Y4KY - High pressure tube nipple UNF
- LH thread



MATERIAL Carbon steel zinc plated, stainless steel on request

#						A	B		
	DN	size	mm	inch		mm	mm	MPa	psi
1Y4KY-9-05	8	-05	7.9	5/16	9/16-18 UNF LH	99	60	140	20300

1YBKY - BSP male nozzle nipple



MATERIAL Carbon steel zinc plated, stainless steel on request


#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1YBKY-2-04	6	-04	6.4	1/4	G 1/8	58	31	10	140	20300
1YBKY-4-04	6	-04	6.4	1/4	G 1/4	62	36	10	140	20300
1YBKY-4-05	8	-05	7.9	5/16	G 1/4	68	35	13	140	20300
1YBKY-6-05	8	-05	7.9	5/16	G 3/8	71	37	17	140	20300

1TMKY – Polyflex Lok components



#	Description
1TMKY-8-05-HPK	Fitting for DN8 hoses incl. caps (refer to chapter D)

101LX – National Pipe Tapered (NPT) male




MATERIAL High strength carbon steel, zinc plated, C: Stainless steel

#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
101LX-4-03	5	-03	4.8	3/16	1/4 NPT	75	33	14	103.5	15000
101LX-4-03C	5	-03	4.8	3/16	1/4 NPT	75	33	14	103.5	15000
101LX-4-04	6	-04	6.4	1/4	1/4 NPT	80	36	14	103.5	15000
101LX-4-04C	6	-04	6.4	1/4	1/4 NPT	80	36	14	103.5	15000
101LX-6-04	6	-04	6.4	1/4	3/8 NPT	80	36	19	103.5	15000
101LX-6-04C	6	-04	6.4	1/4	3/8 NPT	80	36	19	103.5	15000
101LX-4-05	8	-05	7.9	5/16	1/4 NPT	76	31	14	103.5	15000
101LX-4-05C	8	-05	7.9	5/16	1/4 NPT	76	31	14	103.5	15000
101LX-6-06	10	-06	9.5	3/8	3/8 NPT	76	30	19	103.5	15000
101LX-6-06C	10	-06	9.5	3/8	3/8 NPT	76	30	19	103.5	15000
101LX-8-06	10	-06	9.5	3/8	1/2 NPT	81	35	22	103.5	15000
101LX-8-06C	10	-06	9.5	3/8	1/2 NPT	81	35	22	103.5	15000
101LX-8-08	12	-08	12.7	1/2	1/2 NPT	91	37	22	103.5	15000
101LX-8-08C	12	-08	12.7	1/2	1/2 NPT	91	37	22	103.5	15000
101LX-12-12	20	-12	19.0	3/4	3/4 NPT	124	57	35	69.0	10000
101LX-16-16	25	-16	25.4	1	1 NPT	125	64	35	69.0	10000

Design Factor >2:1

192LX / 692LX – BSP female swivel (60° cone)


MATERIAL High strength carbon steel, zinc plated, C: Stainless steel



#						A				
	DN	size	mm	inch		mm	mm		MPa	psi
192LX-4-03	5	-03	4.8	3/16	G 1/4	64	25	22	180	26100
192LX-4-03C	5	-03	4.8	3/16	G 1/4	64	25	22	180	26100
192LX-6-05	8	-05	7.9	5/16	G 3/8	69	25	27	150	21750
192LX-6-05C	8	-05	7.9	5/16	G 3/8	69	25	27	150	21750
192LX-8-06	10	-06	9.5	3/8	G 1/2	66	22	30	140	20300
192LX-8-06C	10	-06	9.5	3/8	G 1/2	66	22	30	140	20300
192LX-8-08	12	-08	12.7	1/2	G 1/2	75	21	30	140	20300
192LX-8-08C	12	-08	12.7	1/2	G 1/2	75	21	30	140	20300
192LX-12-08C	12	-08	12.7	1/2	G 3/4	85	30	32	140	20300
192LX-16-12	20	-12	19.0	3/4	G 1	77	24	41	100	14500
192LX-16-12C4462	20	-12	19.0	3/4	G 1	77	24	41	100	14500
692LX-16-16C	25	-16	25.4	1	G 1	78	25	38	90	13050
192LX-20-16	25	-16	25.4	1	G 1 1/4	78	25	50	90	13050


15YLX / 65YLX – Medium pressure female swivel

MATERIAL Special materials, C: Stainless steel



#						A				
	DN	size	mm	inch		mm	mm		MPa	psi
65YLX-6-3C	5	-03	4.8	3/16	9/16 - 18	78	39	19	138	20000
15YLX-6-04C	6	-04	6.4	1/4	9/16 - 18	72	39	19	138	20000


16YLX – High pressure female swivel




MATERIAL Stainless steel

#	⊙					A	B	J	⌚	
	DN	size	mm	inch		mm	mm	mm	MPa	psi
16YLX-4-03C	5	-03	4.8	3/16	9/16 - 18 UNF	71	33	19	180	26100

1C9LX – Metric female swivel heavy series with O-ring




MATERIAL High strength carbon steel, zinc plated, C: Stainless steel

#	⊙					A	B	J	⌚	
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1C9LX-8-025	4	-025	4.0	5/32	M16x1.5	67	30	22	250	36250
1C9LX-8-025C	4	-025	4.0	5/32	M16x1.5	67	30	22	250	36250
1C9LX-16-03	5	-03	4.8	3/16	M24x1.5	80	38	30	250	36250
1C9LX-10-04	6	-04	6.4	1/4	M18x1.5	76	31	27	170	24650
1C9LX-10-04C	6	-04	6.4	1/4	M18x1.5	76	31	27	170	24650
1C9LX-16-04	6	-04	6.4	1/4	M24x1.5	85	40	30	170	24650
1C9LX-14-05	8	-05	7.9	5/16	M22x1.5	84	40	30	150	21750
1C9LX-16-05	8	-05	7.9	5/16	M24x1.5	84	40	30	150	21750
1C9LX-16-05C	8	-05	7.9	5/16	M24x1.5	84	40	30	150	21750
1C9LX-12-06	10	-06	9.5	3/8	M20x1.5	76	30	27	150	21750
1C9LX-14-06	10	-06	9.5	3/8	M22x1.5	76	30	30	150	21750
1C9LX-14-06C	10	-06	9.5	3/8	M22x1.5	76	30	30	150	21750
1C9LX-16-06	10	-06	9.5	3/8	M24x1.5	80	34	30	150	21750
1C9LX-16-06C	10	-06	9.5	3/8	M24x1.5	80	34	30	150	21750
1C9LX-16-08	12	-08	12.7	1/2	M24x1.5	88	34	30	150	21750
1C9LX-16-08C	12	-08	12.7	1/2	M24x1.5	88	34	30	150	21750
1C9LX-25-12	20	-12	19.0	3/4	M36x2	92	39	46	100	14500
1C9LX-25-12C4462	20	-12	19.0	3/4	M36x2	92	39	46	100	14500
1C9LX-30-16	25	-16	25.4	1	M42x2	98	45	50	90	13050
1C9LX-30-16C4462	25	-16	25.4	1	M42x2	98	45	50	90	13050

1C3LX – Metric female swivel light series


MATERIAL High strength carbon steel, zinc plated, C: Stainless steel




#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1C3LX-8-025	4	-025	4.0	5/32	M14x1.5	63	26	22	220	31900
1C3LX-8-03	5	-03	4.8	3/16	M14x1.5	64	25	22	180	26100
1C3LX-8-03C	5	-03	4.8	3/16	M14x1.5	64	25	22	180	26100
1C3LX-8-04	6	-04	6.4	1/4	M14x1.5	69	25	22	164	23780
1C3LX-8-04C	6	-04	6.4	1/4	M14x1.5	69	25	22	164	23780

1C6LX – Metric female swivel heavy series


MATERIAL High strength carbon steel, zinc plated



#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1C6LX-12-05	8	-05	7.9	5/16	M20x1.5	78	34	27	150	21750


1D9LX – BSP male

MATERIAL High strength carbon steel, zinc plated



#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1D9LX-4-025	4	-025	4.0	5/32	G 1/4	73	36	19	220	31900
1D9LX-4-03	5	-03	4.8	3/16	G 1/4	77	35	19	180	26100
1D9LX-4-04	6	-04	6.4	1/4	G 1/4	80	36	19	164	23,780
1D9LX-4-05	8	-05	7.9	5/16	G 1/4	77	33	19	150	21750
1D9LX-4-06	10	-06	9.5	3/8	G 1/4	76	30	19	140	20300


1Y2LX – Medium pressure tube nipple



MATERIAL Special materials, C: Stainless steel

#						A		B		
	DN	size	mm	inch		mm	mm	MPa	psi	
1Y2LX-4-025	4	-025	4.0	5/32	1/4-28 UNF-LH	94	55	138	20000	
1Y2LX-4-03	5	-03	4.8	3/16	1/4-28 UNF-LH	99	57	138	20000	
1Y2LX-6-025	4	-025	4.0	5/32	3/8 - 24UNF-LH	112	73	138	20000	
1Y2LX-6-03	5	-03	4.8	3/16	3/8 - 24UNF-LH	118	75	138	20000	
1Y2LX-6-03C	5	-03	4.8	3/16	3/8 - 24UNF-LH	118	75	138	20000	
1Y2LX-9-03	5	-03	4.8	3/16	9/16-18 UNF-LH	102	65	138	20000	
1Y2LX-9-03C	5	-03	6.4	1/4	9/16-18 UNF-LH	102	65	138	20000	
1Y2LX-6-04	6	-04	6.4	1/4	3/8 - 24UNF-LH	120	65	138	20000	
1Y2LX-6-04C	6	-04	6.4	1/4	3/8 - 24UNF-LH	109	65	138	20000	
1Y2LX-6-05C	8	-05	7.9	5/16	3/8-24 UNF LH	133	88	138	20000	
1Y2LX-9-05	8	-05	7.9	5/16	9/16 - 18 UNF LH	105	60	138	20000	
1Y2LX-6-06C	10	-06	9.5	3/8	3/8-24 UNF LH	128	82	138	20000	
1Y2LX-9-06C	10	-06	9.5	3/8	9/16 - 18 UNF LH	137	91	138	20000	
1Y2LX-9-08	12	-08	12.7	1/2	9/16 - 18 UNF LH	110	60	138	20000	
1Y2LX-9-08C	12	-08	12.7	1/2	9/16 - 18 UNF LH	110	60	138	20000	
1Y2LX-12-08C	12	-08	12.7	1/2	3/4 - 16 UNF LH	158	104	138	20000	
1Y2LX-12-12C4462	20	-12	19.0	3/4	3/4 - 16 UNF LH	160	100	138	20000	
1Y2LX-16-12C4462	20	-12	19.0	3/4	1-14 UNS LH	181	121	138	20000	
1Y2LX-16-16C4462	25	-16	25.4	1	1-14 UNS LH	181	121	138	20000	


1Y9LX – BSP male for USIT ring




MATERIAL High strength carbon steel, zinc plated, C: Stainless steel

#						A		B		
	DN	size	mm	inch		mm	mm	mm		
1Y9LX-4-03	5	-03	4.8	3/16	G 1/4	72	32	22	180	26100
1Y9LX-4-03C	5	-03	4.8	3/16	G 1/4	72	32	22	180	26100
1Y9LX-6-05	8	-05	7.9	5/16	G 3/8	82	38	27	150	21750
1Y9LX-8-08	12	-08	12.7	1/2	G 1/2	87	32	36	130	18850

1MRLX/6MRLX – Metric female swivel 59° cone




MATERIAL High strength carbon steel, zinc plated


#						A	B			
	DN	size	mm	inch		mm	mm	mm	MPa	psi
1MRLX-6-02	3	-02	3.0	1/32	M12x1,5	43	21	17	250	36250
1MRLX-8-02	3	-02	3.0	1/32	M14x1,5	48	26	22	250	36250
1MRLX-8-025	4	-025	4.0	5/32	M14x1,5	65	34	22	250	36250
6MRLX-6-2AC	4	-025	4.0	5/32	M12x1,5	103	72	17	301	43645
6MRLX-8-2AC	4	-025	4.0	5/32	M14x1,5	103	72	22	301	43645
1MRLX-6-03	5	-03	4.8	3/16	M12x1,5	92	53	17	250	36250
1MRLX-8-03	5	-03	4.8	3/16	M14x1,5	66	26	22	250	36250

Design Factor >2:1


1YALX/1Y4LX/6Y4LX – High pressure tube nipple UNF – LH thread



MATERIAL Special materials, C: Stainless steel

#						A		B		
	DN	size	mm	inch		mm	mm	MPa	psi	
1Y4LX-4-02	3	-02	3.0	1/32	1/4 - 28UNF-LH	63	41	400	58000	
1YALX-1-025	4	-025	4.0	5/32	1/4 - 28UNF-LH	87	50	400	58000	
1YALX-1-025C	4	-025	4.0	5/32	1/4 - 28UNF-LH	87	50	400	58000	
1YALX-3-025	4	-025	4.0	5/32	3/8 - 24UNF-LH	89	50	400	58000	
6Y4LX-4-2AC	4	-025	4.0	5/32	1/4-28 UNF-LH	75	42	400	58000	
6Y4LX-4-2AC-PL	4	-025	4.0	5/32	1/4-28 UNF-LH	70	37	400	58000	
6Y4LX-6-2AC	4	-025	4.0	5/32	3/8-24 UNF-LH	87	54	400	58000	
6Y4LX-6-2AC-PL	4	-025	4.0	5/32	3/8-24 UNF-LH	87	54	400	58000	
1YALX-1-03	5	-03	4.8	3/16	1/4 - 28UNF-LH	92	53	400	58000	
1YALX-1-03C	5	-03	4.8	3/16	1/4 - 28UNF-LH	92	53	400	58000	
1YALX-3-03	5	-03	4.8	3/16	3/8 - 24UNF-LH	99	57	400	58000	
1YALX-3-03C	5	-03	4.8	3/16	3/8 - 24UNF-LH	99	57	400	58000	
1YALX-6-03	5	-03	4.8	3/16	9/16 - 18UNF-LH	108	67	400	58000	
1YALX-6-03C	5	-03	4.8	3/16	9/16 - 18UNF-LH	108	67	400	58000	
1YALX-3-04	6	-04	6.4	1/4	3/8 - 24UNF-LH	102	58	400	58000	
1YALX-3-04C	6	-04	6.4	1/4	3/8 - 24UNF-LH	102	58	400	58000	
1YALX-6-04	6	-04	6.4	1/4	9/16 - 18UNF-LH	112	67	400	58000	
1YALX-3-05C	8	-05	7.9	5/16	3/8 - 24UNF-LH	103	59	400	58000	
1YALX-6-05	8	-05	7.9	5/16	9/16 - 18UNF-LH	110	66	400	58000	
1YALX-6-05C	8	-05	7.9	5/16	9/16 - 18UNF-LH	110	66	400	58000	
1YALX-6-06	10	-06	9.5	3/8	9/16 - 18UNF-LH	106	62	400	58000	
1YALX-6-06C	10	-06	9.5	3/8	9/16 - 18UNF-LH	106	62	400	58000	
1Y4LX-9-08	12	-08	12.7	1/2	9/16 - 18UNF-LH	124	70	400	58000	
1Y4LX-9-08C	12	-08	12.7	1/2	9/16 - 18UNF-LH	124	70	400	58000	


1YMLX – High pressure tube nipple metric – LH thread



MATERIAL High strength carbon steel, zinc plated, C: Stainless steel

#						A	B		
	DN	size	mm	inch				MPa	psi
1YMLX-6-025	4	-025	4.0	5/32	M14x1.5-LH	103	72	250	36250
1YMLX-6-04	6	-04	6.4	1/4	M14x1.5-LH	112	80	250	36250
1YMLX-6-05	8	-05	7.9	5/16	M14x1.5-LH	110	66	250	36250
1YMLX-11-08	12	-08	12.7	1/2	M18x1.5-LH	120	65	250	36250


1AYLX / 6AYLX – Type “M” female swivel



MATERIAL High strength carbon steel, zinc plated, C: Stainless steel


#						A	B			
	DN	size	mm	inch					MPa	psi
1AYLX-6-02	3	-02	3.0	1/8	9/16 - 18UNF	48	26	22	250	36250
1AYLX-6-025	4	-025	4.0	5/32	9/16 - 18 UNF	64	33	22	250	36250
1AYLX-6-025C	4	-025	4.0	5/32	9/16 - 18 UNF	64	33	22	250	36250
1AYLX-6-03	5	-03	4.8	3/16	9/16 - 18UNF	66	26	22	250	36250
1AYLX-6-03C	5	-03	4.8	3/16	9/16 - 18 UNF	67	26	22	250	36250
1AYLX-6-04	6	-04	6.4	1/4	9/16 - 18UNF	61	29	22	250	36250
1AYLX-6-04C	6	-04	6.4	1/4	9/16 - 18UNF	61	29	22	250	36250
1AYLX-8-05	8	-05	7.9	5/16	3/4 - 16UNF	74	30	27	250	36250
1AYLX-8-05C	8	-05	7.9	5/16	3/4 - 16 UNF	70	31	27	250	36250
1AYLX-8-06	10	-06	9.5	3/8	3/4 - 16UNF	70	26	27	250	36250
1AYLX-8-06C	10	-06	9.5	3/8	3/4 - 16 UNF	70	25	27	250	36250
1AYLX-11-08	12	-08	12.7	1/2	1 - 12 UNF	80	27	32	250	36250
1AYLX-11-08C	12	-08	12.7	1/2	1 - 12 UNF	80	27	32	250	36250
1AYLX-16-12	20	-12	19.0	3/4	1 5/16-12UNF	82	29	41	250	36250
1AYLX-16-12C4462	20	-12	19.0	3/4	1 5/16-12UNF	82	29	41	250	36250
6AYLX-6-2AC	4	-025	4.0	5/32	9/16 - 18 UNF	64	33	17	301	43645
6AYLX-16-16C	25	-16	25.4	1	1 5/16 - 12 UNF	100	40	38	250	36250

6YHLX – UNF male nozzle nipple




MATERIAL Stainless steel

NOTE ProLance fitting

#						A	B	H		
	DN	size	mm	inch		mm	mm	mm	MPa	psi
6YHLX-4-02-PL	3	-02	3.0	1/32	1/4-28 UNF	52	30	8	280	40600
6YHLX-4-2AC-PL	4	-025	4.0	5/32	1/4 - 28 UNF	58	26	8	301	43645
6YHLX-4-2AC-PL-LH	4	-025	4.0	5/32	1/4 - 28 UNF LH	58	26	8	301	43645
6YHLX-6-2AC-PL-LH	4	-025	4.0	5/32	3/8-24 UNF LH	62	30	10	301	43645
6YHLX-4-3C-PL	5	-03	4.8	3/16	1/4 - 28 UNF	62	29	10	280	40600
6YHLX-4-3C-PL-LH	5	-03	4.8	3/16	1/4 - 28 UNF LH	62	29	10	280	40600
6YHLX-6-3C-PL	5	-03	4.8	3/16	3/8 - 24 UNF	65	32	10	280	40600
6YHLX-6-3C-PL-LH	5	-03	4.8	3/16	3/8 - 24 UNF LH	65	32	10	280	40600
6YHLX-6-4C-PL	6	-04	6.4	1/4	3/8 - 24 UNF	66	36	11	280	40600
6YHLX-9-4C-PL	6	-04	6.4	1/4	9/16-18 UNF	67	37	16	280	40600
6YHLX-6-4C-PL-LH	6	-04	6.4	1/4	3/8 - 24 UNF LH	66	36	11	280	40600
6YHLX-9-5C-PL	8	-05	7.9	5/16	9/16 - 18 UNF	80	36	16	280	40600
6YHLX-9-5C-PL-LH	8	-05	7.9	5/16	9/16 - 18 UNF LH	80	36	16	280	40600

Design Factor >2:1

6HYLX – UNF female
for water jetting nozzle



MATERIAL Stainless steel
NOTE ProLance fitting

#						A	B	H		
	DN	size	mm	inch		mm	mm	mm	MPa	psi
6HYLX-4-2AC-PL	4	-025	4.0	5/32	1/4 - 28 UNF	51	19	9	301	43645
6HYLX-4-2AC-PL-LH	4	-025	4.0	5/32	1/4 - 28 UNF LH	51	19	9	301	43645
6HYLX-6-2AC-PL-LH	4	-025	4.0	5/32	3/8 - 24 UNF-LH	49	21	11	301	43645
6HYLX-4-3C-PL	5	-03	4.8	3/16	1/4 - 28 UNF	52	19	9	280	40600
6HYLX-4-3C-PL-LH	5	-03	4.8	3/16	1/4 - 28 UNF LH	52	19	9	280	40600
6HYLX-6-3C-PL	5	-03	4.8	3/16	3/8 - 24 UNF	56	23	11	280	40600
6HYLX-6-3C-PL-LH	5	-03	4.8	3/16	3/8 - 24 UNF LH	56	23	11	280	40600
6HYLX-6-4C-PL	6	-04	6.4	1/4	3/8 - 24 UNF	58	25	11	280	40600
6HYLX-6-4C-PL-LH	6	-04	6.4	1/4	3/8 - 24 UNF LH	58	25	11	280	40600
6HYLX-9-5C-PL	8	-05	7.9	5/16	9/16 - 18 UNF	72	28	17	280	40600
6HYLX-9-5C-PL-LH	8	-05	7.9	5/16	9/16 - 18 UNF	72	28	17	280	40600