

GST II B LACK 20

Parker Global Product

Designed for compressed air with traces of oil in industrial application. Also suitable in agriculture, construction, and general industry for water, mild chemicals and non aggressive fluids. Not to be used with oil or refined fuel.

Hose Construction

Tube: Black EPDM, antistatic rubber compound.
 Reinforcement: Synthetic textile yarns.
 Cover: Black, smooth EPDM rubber compound resistant to abrasion, heat and ozone

Temperature Range

-40 °C (-40 °F) to +100 °C (+212 °F)



- Nitrosamine free
- Permanent fittings capability
- EPDM compound suitable also for oil mist
- All sizes on stock
- Burst Pressure Value 4:1



Tolerances

According to UNI EN ISO 1307
 Refer to Technical Handbook on page TH34

Part Number				Working Pressure					in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	min. Bend Radius mm		
IH709325300/100	6.5	14	2.0	300.0	20	0.16	50	Y	
IH709331300/100	8	16	2.0	300.0	20	0.20	65	Y	
IH709338300/100	9.5	17.5	2.0	300.0	20	0.23	75	Y	
IH709350304/100	13	22	2.0	300.0	20	0.36	105	Y	
IH709363304/100	16	27	2.0	300.0	20	0.52	130	Y	
IH709375304/40	19	29.5	2.0	300.0	20	0.56	150	Y	
IH7093100304/40	25	36.5	2.0	300.0	20	0.75	200	Y	



SERIES 7093 GST® II ... ID (..mm) 300 PSI (20 bar) MAX WP