

GST II RED 15

Parker Global Product

In agriculture, construction, air tool lubricant systems and general industrial for air (including oil mist), mild chemicals and water. Suitable for MRO and OEM channel. Not to be used with oil or refined fuel..

Hose Construction

Tube: Black EPDM, antistatic rubber compound.
Reinforcement: Synthetic textile yarns
Cover: Red, smooth EPDM insulating rubber compound resistant to abrasion, heat and ozone

Temperature Range

-40 °C (-40 °F) to +100 °C (+212 °F)



- Nitrosamine free
- Permanent fittings capability
- EPDM compound suitable also for oil mist
- Design Factor 4:1



Tolerances

According to UNI EN ISO 1307
 Refer to Technical Handbook on page TH34

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource-euro.

Part Number	I.D. (mm)	O.D. (mm)	Max. Working Pressure			Weight kg/m	min. Bend Radius mm
			MPa	psi	bar		
IH709225200/40	6.5	13	1.5	200.0	15	0.13	50
IH709231200/40	8	15	1.5	200.0	15	0.16	65
IH709238200/40	9.5	17	1.5	200.0	15	0.20	75
IH709250200/40	13	21	1.5	200.0	15	0.29	105
IH709263200/40	16	25	1.5	200.0	15	0.36	130
IH709275200/40	19	28	1.5	200.0	15	0.49	150
IH7092100200/40	25	36	1.5	200.0	15	0.69	200
IH7092125204/40	32	45	1.5	200.0	15	1.15	230
IH7092150204/40	38	52	1.5	200.0	15	2.76	250

Hose layline example

	SERIES 7092 GST® II ... ID (...mm) 200 PSI (15 bar) MAX WP
--	--