



JUMBO

Suitable for the discharge of hot and cold water, air and light-chemical media in many industrial and agricultural applications.

Hose Construction

- Tube:** Black, smooth EPDM antistatic nitrosamine free rubber compound
- Reinforcement:** Synthetic textile yarns
- Cover:** Black, smooth EPDM rubber compound insulating with nitrosamine free rubber compound with three red, longitudinal and different stripes, resistant to abrasion, heat and weathering

Temperature Range

-40 °C (-40 °F) to +120 °C (+248 °F)



- Agriculture, construction and general industrial
- Long lasting embossed type branding
- Three red stripes for easy hose identification
- Nitrosamine free
- Design Factor 3:1



Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at www.parker.com/crimpsource-euro.

Part Number			 Max. Working Pressure			 Weight	 min. Bend Radius
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	mm
IH30116500/40	13	19	2.0	300.0	20	0.21	75
IH30116501/40	15	22	2.0	300.0	20	0.31	90
IH30116502/40	19	27	2.0	300.0	20	0.60	110
IH30116504/40	25	34	2.0	300.0	20	0.74	150

Hose layline example

