

KISAN TROLLEY HOSE



# Part Number	Hose I.D		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
KTPM-6PM	3/8	9.5	15.1	17.4	1740	12.0	5.0	130	0.21	0.31
KTPM-8PM	1/2	12.7	18.3	20.3	1740	12.0	7.0	180	0.26	0.38

Application : Petroleum base hydraulic fluids and lubricating oils.
Inner Tube : Synthetic Rubber
Reinforcement : One wire braid.
Cover : Synthetic Rubber.
Temp. Range : -40°F to +212°F (-40°C to +100°C)

SLIM HOLE HOSE (3 Wire)



# Part Number	Hose I.D		Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
3WIREPM-40PM	2-1/2	63.5	86.0	1500	10.3	30.0	762	3.42	5.05

Application : Designed for rotary hole on oil rigs and hydraulic applications.
Inner Tube : Synthetic oil resistant rubber
Reinforcement : Three braid high tensile steel wire
Cover : Oil & abrasion resistant synthetic rubber
Temp. Range : - 40°F to +250°F (- 40°C to +121°C)

SLIM HOLE HOSE (4 Wire)



# Part Number	Hose I.D		Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
4WIREPM-40PM	2-1/2	63.5	86.0	2600	18.0	30.0	762	4.37	6.45
4WIREPM-48PM	3	76.2	99.1	1375	9.5	43.5	1105	4.55	6.72

Application : Designed for rotary hole on oil rigs and hydraulic applications.
Inner Tube : Synthetic oil resistant rubber
Reinforcement : Four braid high tensile steel wire
Cover : Oil & abrasion resistant synthetic rubber
Temp. Range : - 40°F to +250°F (- 40°C to +121°C)