

SPIRABLAST 36K™

WaterJetting Hose



# Part Number	Hose I.D.		Hose R.O.D.	Hose O.D.	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	bar	inch	mm	lbs/ft	kg/m
SB36KPM-6PM	3/8	9.5	19.0	22.8	14500	1000	7.9	200	0.70	1.03
SB36KPM-8PM	1/2	12.7	23.1	27.2	14500	1000	11.9	300	0.90	1.33

Application:

Water blast / Jetting.

Construction:

Inner Tube : CR - Synthetic rubber
Reinforcement : Four high tensile steel wire spirals
Outer Cover : SBR - Synthetic rubber

Temp. Range

0°C to +80°C Continuous
(+32°F to + 176 °F Continuous)

SPIRABLAST 40K™

WaterJetting Hose



# Part Number	Hose I.D.		Hose R.O.D.	Hose O.D.	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	bar	inch	mm	lbs/ft	kg/m
SB40KPM-6PM	3/8	9.5	19.0	23.0	15950	1100	5.9	150	0.67	1.01
SB40KPM-8PM	1/2	12.7	23.0	27.0	15950	1100	9.0	230	0.90	1.34

Application:

Water blast / Jetting.

Construction:

Inner Tube : CR - Synthetic rubber
Reinforcement : Four high tensile steel wire spirals
Outer Cover : SBR - Synthetic rubber

Temp. Range

0°C to +80°C Continuous
(+32°F to + 176 °F Continuous)

SPIRABLAST 50K™

Water Jetting Hose



# Part Number	Hose I.D.		Hose R.O.D.	Hose O.D.	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	bar	inch	mm	lbs/ft	kg/m
SB50KPM-6PM	3/8	9.5	22.7	25.5	20000	1380	7.9	200	-	-
SB50KPM-8PM	1/2	12.7	27.7	30.7	20000	1380	11.9	300	1.52	2.25

Application:

Water blast / Jetting

Construction:

Inner Tube : CR- Synthetic rubber
Reinforcement : Four high tensile steel wire spirals
Outer Cover : SBR - Synthetic rubber

Temp. Range

0°C to +80°C Continuous
(+32°F to + 176 °F Continuous)