

ALTERNATIVE /
MARINE / FUEL

SS25UL

- Low-pressure service with liquefied petroleum gas
- UL Standard 21 certification
- Oil and LPG resistant synthetic fiber cover
- Compatible with 26 Series Parkrimp style fittings

SS25UL

Transportation – Liquefied Petroleum Gas

UL 21 / NFPA 58



view on web page

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 26 Series	Field Attachable 20/22 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m		
SS25UL-4	3/16	5	0.52	13,2	350	2,4	0.75	20	0.11	0,16	Link	Link
SS25UL-5	1/4	6,3	0.58	14,8	350	2,4	1	25	0.13	0,19	Link	Link
SS25UL-6	5/16	8	0.68	17,2	350	2,4	1-1/4	30	0.18	0,27	Link	Link
SS25UL-8	13/32	10	0.77	19,5	350	2,4	1-3/4	45	0.21	0,31	Link	Link
SS25UL-10	1/2	12,5	0.92	23,4	350	2,4	2-1/4	55	0.29	0,43	Link	Link
SS25UL-12	5/8	16	1.08	27,4	350	2,4	2-3/4	70	0.37	0,55	Link	Link

Application: Liquefied petroleum gas (LPG).**Inner Tube:** Synthetic rubber.**Reinforcement:** One fiber braid and one stainless steel wire braid.**Cover:** Fiber braid.**Temperature Range:** -40°F to +250°F (-40°C to +121°C).**Fittings:** 26 Series - pg. 63.
20 Series - pg. 200.
22 Series - pg. 216.**WARNING**

The products described in this catalog can expose you to chemicals, including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

SS25UL-AGA

Transportation – Liquefied Petroleum Gas

AS / NZS 1869-2012 CLASS D



view on web page

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp 26 Series	Field Attachable 20/22 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m		
SS25UL-4-AGA	3/16	5	0.52	13,2	375	2,6	0.75	20	0.11	0,16	Link	Link
SS25UL-6-AGA	5/16	8	0.68	17,2	375	2,6	1-1/4	30	0.18	0,27	Link	Link
SS25UL-8-AGA	13/32	10	0.77	19,5	375	2,6	1-3/4	45	0.21	0,31	Link	Link

FACTORY MADE HOSE ASSEMBLIES ONLY. Contact Hose Products Division for more information.**Application:** Liquefied petroleum gas (LPG).**Inner Tube:** Synthetic rubber.**Reinforcement:** One fiber braid and one stainless steel wire braid.**Cover:** Fiber braid.**Temperature Range:** -40°F to +250°F (-40°C to +121°C).**Fittings:** 26 Series - pg. 63.
20 Series - pg. 200.
22 Series - pg. 216.

- See Section 2 for Field Attachable Assembly Instructions.
- See Section 3 for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section 18.

WARNING

The products described in this catalog can expose you to chemicals, including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.