


[Click here for CADs, Support Resources or to Configure Parts Online](#)

## XHLO

Male Adapter  
37° Flare / ORFS




| TUBE<br>FITTING<br>PART # | END SIZE   |            | FF<br>(in.) | H<br>HEX<br>(in.) | Dynamic<br>Pressure<br>(x 1,000 PSI) |     |
|---------------------------|------------|------------|-------------|-------------------|--------------------------------------|-----|
|                           | 1<br>(in.) | 2<br>(in.) |             |                   | -S                                   | -SS |
| 4 XHLO                    | 1/4        | 1/4        | 1.25        | 5/8               | 7.5                                  | 9.0 |
| 6 XHLO                    | 3/8        | 3/8        | 1.34        | 3/4               | 6.0                                  | 7.2 |
| 8 XHLO                    | 1/2        | 1/2        | 1.55        | 7/8               | 6.0                                  | 7.2 |
| 10 XHLO                   | 5/8        | 5/8        | 1.83        | 1 1/16            | 5.0                                  | 6.0 |
| 12 XHLO                   | 3/4        | 3/4        | 2.05        | 1 1/4             | 5.0                                  | 6.0 |
| 16 XHLO                   | 1          | 1          | 2.16        | 1 1/2             | 4.5                                  | 5.4 |
| 20 XHLO                   | 1 1/4      | 1 1/4      | 2.29        | 1 3/4             | 4.0                                  | 4.8 |
| 24 XHLO                   | 1 1/2      | 1 1/2      | 2.48        | 2 1/8             | 3.0                                  | 3.6 |

**WARNING:** This product can expose you to chemicals including Lead and Lead Compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## LOHX6

Swivel Adapter  
37° Flare Swivel / ORFS




\*LL – End to base of flare

| TUBE<br>FITTING<br>PART # | END SIZE   |            | C3<br>HEX<br>(in.) | H<br>HEX<br>(in.) | LL<br>Ref.<br>(in.) | Dynamic<br>Pressure<br>(x 1,000 PSI) |     |
|---------------------------|------------|------------|--------------------|-------------------|---------------------|--------------------------------------|-----|
|                           | 1<br>(in.) | 2<br>(in.) |                    |                   |                     | -S                                   | -SS |
| 4 LOHX6                   | 1/4        | 1/4        | 9/16               | 5/8               | 0.89                | 7.5                                  | 9.0 |
| 6 LOHX6                   | 3/8        | 3/8        | 11/16              | 3/4               | 1.06                | 5.0                                  | 6.0 |
| 8 LOHX6                   | 1/2        | 1/2        | 7/8                | 7/8               | 1.21                | 5.0                                  | 6.0 |
| 10 LOHX6                  | 5/8        | 5/8        | 1                  | 1 1/16            | 1.40                | 5.0                                  | 6.0 |
| 12 LOHX6                  | 3/4        | 3/4        | 1 1/4              | 1 1/4             | 1.48                | 5.0                                  | 6.0 |
| 16 LOHX6                  | 1          | 1          | 1 1/2              | 1 1/2             | 1.64                | 3.6                                  | 4.3 |
| 20 LOHX6                  | 1 1/4      | 1 1/4      | 2                  | 1 3/4             | 1.77                | 3.6                                  | 4.3 |

**WARNING:** This product can expose you to chemicals including Lead and Lead Compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## XHL6

Male Swivel Adapter  
ORFS Swivel / 37° Flare




| TUBE<br>FITTING<br>PART # | END SIZE   |            | B<br>HEX<br>(in.) | FF<br>(in.) | H<br>HEX<br>(inch)<br>(in.) | Dynamic<br>Pressure<br>(x 1,000 PSI) |     |
|---------------------------|------------|------------|-------------------|-------------|-----------------------------|--------------------------------------|-----|
|                           | 1<br>(in.) | 2<br>(in.) |                   |             |                             | -S                                   | -SS |
| 4 XHL6                    | 1/4        | 1/4        | 11/16             | 1.50        | 5/8                         | 7.5                                  | 9.2 |
| 6 XHL6                    | 3/8        | 3/8        | 13/16             | 1.61        | 3/4                         | 6.0                                  | 7.2 |
| 8 XHL6                    | 1/2        | 1/2        | 15/16             | 1.90        | 7/8                         | 6.0                                  | 7.2 |
| 10 XHL6                   | 5/8        | 5/8        | 1 1/8             | 2.20        | 1 1/16                      | 5.0                                  | 6.0 |
| 12 XHL6                   | 3/4        | 3/4        | 1 3/8             | 2.50        | 1 1/4                       | 5.0                                  | 6.0 |
| 16 XHL6                   | 1          | 1          | 1 5/8             | 2.66        | 1 1/2                       | 4.5                                  | 5.4 |
| 20 XHL6                   | 1 1/4      | 1 1/4      | 1 7/8             | 2.80        | 1 11/16                     | 4.0                                  | 4.8 |

**WARNING:** This product can expose you to chemicals including Lead and Lead Compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## LOEX6

Swivel Elbow  
ORFS / 37° Flare Swivel



\* JJ – Across wrench flats

| TUBE<br>FITTING<br>PART # | END SIZE   |                | JJ<br>(in.) | M<br>(in.) | M5<br>(in.) | Dynamic<br>Pressure<br>(x 1,000 PSI) |     |
|---------------------------|------------|----------------|-------------|------------|-------------|--------------------------------------|-----|
|                           | 1<br>(in.) | 2<br>UN/UNF-2B |             |            |             | -S                                   | -SS |
| 4 LOEX6                   | 1/4        | 1/4            | 9/16        | 0.85       | 1.08        | 7.5                                  | 7.5 |
| 6 LOEX6                   | 3/8        | 3/8            | 3/4         | 0.98       | 1.25        | 5.0                                  | 5.0 |
| 8 LOEX6                   | 1/2        | 1/2            | 3/4         | 1.10       | 1.38        | 5.0                                  | 5.0 |
| 10 LOEX6                  | 5/8        | 5/8            | 1 1/16      | 1.31       | 1.63        | 5.0                                  | 5.0 |
| 12 LOEX6                  | 3/4        | 3/4            | 1 3/16      | 1.47       | 1.80        | 5.0                                  | 5.0 |
| 16 LOEX6                  | 1          | 1              | 1 7/16      | 1.64       | 2.00        | 4.0                                  | 4.0 |
| 20 LOEX6                  | 1 1/4      | 1 1/4          | 1 5/8       | 1.76       | 2.31        | 3.6                                  | 3.6 |
| 24 LOEX6                  | 1 1/2      | 1 1/2          | 1 7/8       | 1.92       | 2.59        | 3.0                                  | 3.0 |

Dimensions and pressures for reference only, subject to change.